PermaCem 2.0

Product code: 213366, 213367, 213368 (1060_GHS)

Page 1 of 4

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

PermaCem 2.0

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company Name:	DMG AMERICA LLC
Address:	242 South Dean Street
City, State, Zip Code:	Englewood, NJ. 07631
Telephone:	(800) 662-6383
email address:	Info@dmg-america.com
Website:	www.dmg-america.com

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Hazard categories:

Organic peroxide: Org. Perox. B Serious eye damage/eye irritation: Eye Dam. 1 Respiratory/skin sensitization: Skin Sens. 1 Hazard Statements: May cause respiratory irritation. Causes serious eye damage. May cause an allergic skin reaction.

2.2. Label elements

Signal word: Pictograms:

Danger GHS02-GHS05-GHS07



Hazard statements

H335	May cause respiratory irritation.
H318	Causes serious eye damage.
H317	May cause an allergic skin reaction.

Precautionary statements

P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if
	present and easy to do. Continue rinsing.
P302+P352	IF ON SKIN: Wash with plenty of water.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

PermaCem2

Product code: 1060

Chemical characterization

chemical characterization (preparation): Acrylate.-resin. Silicon dioxide.

name		CAS		%
UDMA TEDMA	 	n.a. 109-16-0	 	5 - 10 4 - 7
Bis-GMA BPO		1565-94-2 94-36-0		< 2.5 < 2.5

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Move victim to fresh air. Put victim at rest and keep warm.

After contact with skin

After contact with skin, wash immediately with: Water and soap.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After ingestion

Immediately get medical attention.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water fog. Extinguishing powder. Sand. Foam. Carbon dioxide (CO2).

Unsuitable extinguishing media

High power water jet.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation. Wear suitable protective clothing.

6.2. Environmental precautions

Do not empty into drains or the aquatic environment.

6.3. Methods and material for containment and cleaning up

Collect mechanically.

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed. Wear suitable protective clothing and gloves. Avoid contact with eyes.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Store only in original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Page 2 of 4

PermaCem2

Product code: 1060

8.2. Exposure controls



Protective and hygiene measures

Take off immediately all contaminated clothing. When using do not eat or drink.

Eye/face protection

Tightly sealed safety glasses.

Hand protection

Tested protective gloves are to be worn: Suitable material: NBR (Nitrile rubber).

Respiratory protection

The following must be prevented: inhalation.

SECTION 9: Physical and chemical properties

<u>9.1.</u> Inf ...

0.1. Information on basic physi	ical and chemical properties		
Physical state:	Paste		
Colour:	yellow		
Odour:	like: ester		
		Test metho	bd
Changes in the physical sta	te		
Initial boiling point and boiling	g range:	> 180 °C	
Zersetzungspunkt:		> 180 °C	
Flash point:		95 °C	
Vapour pressure:		1 hPa	
(at 20 °C)			
Density:		1,8 g/cm³	
Water solubility: (at 20 °C)		60 g/L	
Vapour density:		> 1	
()		> 1	

SECTION 10: Stability and reactivity

10.4. Conditions to avoid

heat. Light. Decompostion takes place from temperatures above: 180 °C

10.5. Incompatible materials

Keep away from strong acids, leachates, heavy metal salts and reducing materials.

10.6. Hazardous decomposition products

Can be released in case of fire: Gas / vapours, irritant. (Acrylate., pungent)

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Sensitising effects

May cause sensitization by skin contact.

Additional information on tests

Contains Methacrylic esters.: May produce an allergic reaction.

Page 3 of 4

PermaCem2

Product code: 1060

Page 4 of 4

SECTION 12: Ecological information

12.2. Persistence and degradability

Do not empty into drains or the aquatic environment. Leakage into the environment must be prevented. Preparation not tested.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Can be burnt together with household waste in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge. Paste: Carry out a burning of harzardous waste according to official regulations.

Waste disposal number of waste from residues/unused products

180106 WASTES FROM HUMAN OR ANIMAL HEALTH CARE AND/OR RELATED RESEARCH (except kitchen and restaurant wastes not arising from immediate health care); wastes from natal care, diagnosis, treatment or prevention of disease in humans; chemicals consisting of or containing dangerous substances

Classified as hazardous waste.

SECTION 14: Transport information

Other applicable information

Not a hazardous material with respect to these transportation regulations.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulatory information

Water contaminating class (D):

1 - slightly water contaminating

SECTION 16: Other information

Relevant H- and EUH-phrases (Number and full text)

H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
Europhan Information	

Further Information

The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.